

Orient Jade white glass

Meeting Your Aesthetics Needs

Description

Orient Jade white glass, that's unique requirements of environmental friendly, return to nature and brightness have been met since the birth of Jingniu Jade. It is a rare product and brings fresh style to house decoration and can be widely used to inner or outer decoration of hotel, buildings, aerodromes, undergrounds, hospitals, banks and villas.

Applications

Orient Jade white glass is suitable for all interior and outside surfaces where colour contributes to enhancing an area, including damp or humid rooms such as bathrooms and kitchens.

Orient Jade white glass can be used in domestic and commercial locations such as offices, hotels, museums, theatres and cinemas, for :

- Wall panelling and column cladding
- Furniture
- Cupboard doors
- Splashbacks.

Specification

- **Color:** Jade white glass
- **Thickness:** 6mm-12mm
- **size:** 1500×2440, 1500×2000, 1500×1000, 1500×800, 1500×600, 900×900, 800×800, 600×600mm

Performance

- Bulk density: 2.35—2.45 g/cm³
- Water-absorptivity: 0%
- Compressive strength: ≥50 MPa
- Gloss degree: Gloss ≥95
- Radioactivity: A-grade decorate material standard of China, no limited of use
- Elasticity coefficient: ≥50 Gpa
- Acid and alkali resistance: 650h, K≤0.5% no change of appearance
- Thermal expandability coefficient:(30-200℃), ×10-6 K-1 80—95

Processed product Variations

Like Clear float glass, Noval Jade white glass can be :

- cut
- edgeworked
- drilled.
- Tempered
- Laminated
- Silk-screen

Installation Guidelines

Installation

Orient Jade white glass is intended for interior use only and must be installed in accordance with current national regulations and good practice.

Fixing

- Mechanically fixed, in channels or with clips or point-fixings
- Adhesive fixing using neutral translucent glues or white double-sided adhesive pads. If there is any doubt, tests must be carried out to check the compatibility of the adhesive.

Special precautions

For optimum installation care must be taken to:

- Ensure the surfaces is flat, clean, dry and free from any harsh substances
- In particular light colours should be used against a uniformly pale surface
- Provide a space of 1 to 2 mm between adjacent sheets
- Avoid placing the product near a source of intense heat (in a kitchen: directly behind the cooker hob or where it could come into contact with very hot utensils)

Maintenance

Orient color lacquered glass must be cleaned using a clean, soft cloth and a conventional cleaning product for glass (neutral product with no abrasive particles).

Range

